

CLAIMS

1. A fuel cell, comprising:
a membrane electrode assembly, wherein the membrane electrode assembly
5 comprises:
an anode,
a cathode, and
an electrolyte disposed between and in intimate contact with the anode and the
cathode; and
10 a layer of porous gas diffusion material disposed on a first surface of the
membrane electrode assembly;
wherein porosity of the porous gas diffusion material at localized areas on the
porous gas diffusion layer decreases from a first value to a second value in response to
a decrease in temperature at corresponding areas on the membrane electrode assembly
15 adjacent to the porous gas diffusion layer.
2. The fuel cell as described in claim 1, wherein the layer of porous gas diffusion
material is electrically conductive and is in thermal contact with the first surface of
the membrane electrode assembly.
20
3. The fuel cell as described in claim 2, further comprising a current collector,
wherein the porous gas diffusion layer is interposed between the current collector and
the membrane electrode assembly.
- 25 4. The fuel cell as described in claim 1, wherein the porous gas diffusion material
further comprises a layer made of electrically conductive materials distributed such
that the resulting layer is micro or nano porous.
5. The fuel cell as described in claim 4, wherein the electrically conductive
30 materials is a combination of one or more elements selected from the group consisting
of metal fibers exhibiting positive coefficient of thermal expansion, polymer fibers
exhibiting positive coefficient of thermal expansion, thermoresponsive polymers

exhibiting positive swelling in gel form, thermoresponsive polymers exhibiting positive swelling in fibrous form, thermoresponsive polymers exhibiting negative swelling in gel form and thermoresponsive polymers exhibiting negative swelling in fibrous form.

5

6. The fuel cell as described in claim 1, wherein the porous gas diffusion material further comprises:

a core layer made of materials distributed such that the resulting layer is micro or nano porous; and

10

a conductive material disposed over or embedded in the core layer such that the resulting layer is electrically conductive.

15

7. The fuel cell as described in claim 6, wherein the core layer material is a combination of one or more elements selected from the group consisting of metal fibers exhibiting positive coefficient of thermal expansion, polymer fibers exhibiting positive coefficient of thermal expansion, thermoresponsive polymers exhibiting positive swelling in gel form, thermoresponsive polymers exhibiting positive swelling in fibrous form, thermoresponsive polymers exhibiting negative swelling in gel form and thermoresponsive polymers exhibiting negative swelling in fibrous form.

20

8. The fuel cell as described in claim 1, further comprising a current collector interposed between the porous gas diffusion layer and a second surface of the membrane electrode assembly.

25

9. The fuel cell as described in claim 1, wherein porosity of the porous gas diffusion material at localized areas on the porous gas diffusion layer further decreases from the first value to the second value in response to a trigger condition at corresponding areas on the membrane electrode assembly adjacent to the porous gas diffusion layer,

30

wherein the trigger condition is created in response to a combination of one or more elements selected from the group consisting of temperature, pH, hydrogen concentration, electrolyte water content, electrolyte thickness, electrolyte ionic

conductivity and electrolyte electronic conductivity of the membrane electrode assembly adjacent to the porous gas diffusion layer, crossing a threshold value.

10. A fuel cell, comprising:

a membrane electrode assembly, wherein the membrane electrode assembly comprises:

an anode,

5 a cathode, and

an electrolyte disposed between and in intimate contact with the anode and the cathode; and

a layer of variable porosity gas diffusion material disposed on a first surface of the membrane electrode assembly;

10 wherein porosity of the variable porosity gas diffusion material at localized areas on the variable porosity gas diffusion layer correlates to a temperature differential from a threshold value at corresponding areas on the membrane electrode assembly side adjacent to the variable porosity gas diffusion layer, and further wherein the porosity of the porous gas diffusion material decreases as the temperature
15 differential increases.

11. The fuel cell as described in claim 10, wherein the layer of variable porosity gas diffusion material is electrically conductive and is in thermal contact with the first surface of the membrane electrode assembly.

20

12. The fuel cell as described in claim 11, further comprising a current collector, wherein the variable porosity gas diffusion layer is interposed between the current collector and the membrane electrode assembly.

25 13. The fuel cell as described in claim 10, wherein the variable porosity gas diffusion material further comprises a layer made of electrically conductive materials distributed such that the resulting layer is micro or nano porous.

14. The fuel cell as described in claim 13, wherein the electrically conductive
30 material is a combination of one or more elements selected from the group consisting of metal fibers exhibiting positive coefficient of thermal expansion, polymer fibers exhibiting positive coefficient of thermal expansion, thermoresponsive polymers exhibiting positive swelling in gel form, thermoresponsive polymers exhibiting

positive swelling in fibrous form, thermoresponsive polymers exhibiting negative swelling in gel form and thermoresponsive polymers exhibiting negative swelling in fibrous form.

- 5 15. The fuel cell as described in claim 10, wherein the variable porosity gas diffusion material further comprises:

 a core layer made of materials distributed such that the resulting layer is micro or nano porous; and

- a conductive material disposed over or embedded in the core layer such that the
10 resulting layer is electrically conductive.

16. The fuel cell as described in claim 15, wherein the core layer material is a combination of one or more elements selected from the group consisting of metal fibers exhibiting positive coefficient of thermal expansion, polymer fibers exhibiting
15 positive coefficient of thermal expansion, thermoresponsive polymers exhibiting positive swelling in gel form, thermoresponsive polymers exhibiting positive swelling in fibrous form, thermoresponsive polymers exhibiting negative swelling in gel form and thermoresponsive polymers exhibiting negative swelling in fibrous form.

- 20 17. The fuel cell as described in claim 10, further comprising a current collector interposed between the variable porosity gas diffusion layer and a second surface of the membrane electrode assembly.

18. A method of operating a fuel cell, comprising the steps of:
forming a membrane electrode assembly by disposing an electrolyte between
and in intimate contact with an anode and a cathode;
5 disposing a layer of variable porosity material on a first surface of the
membrane electrode assembly;
activating the membrane electrode assembly by supplying reactants to the
membrane electrode assembly; and
selectively limiting amount of reactants reaching localized areas of the
10 membrane electrode assembly surface using the variable porosity material, wherein the
selectively limiting is accomplished by changing the porosity at localized areas of the
variable porosity material from a first value to a second value in response to a decrease
in temperature at areas of the membrane electrode assembly adjacent to the localized
areas of the variable porosity material.
15
19. The method of claim 18, wherein the selectively limiting is further
accomplished by changing the porosity at localized areas of the variable porosity
material from the first value to the second value in response to changing a combination
of one or more elements selected from the group consisting of temperature, pH,
20 hydrogen concentration, electrolyte water content, electrolyte thickness, electrolyte
ionic conductivity and electrolyte electronic conductivity of the membrane electrode
assembly adjacent to the variable porosity material layer, crossing a threshold value.